

NEW



RADOLID®



• NOW AVAILABLE •

DSW NUT CAPS

The DSW bolt and nut caps are produced in a two component molding. These new caps feature a captive soft sealing lip molded from 70% PE and 30% Evoprene; an elastic, flexible material that can be adapted to suit the base, hence providing an excellent seal. The cap body is made from a more solid material, guaranteeing a reliable and stable hold. These caps afford a much better and tighter seal for preventing moisture from penetrating under Radolid caps.

- Suitable for offshore applications, high humidity industries, and other damp conditions
- Comes in a number of different designs
- Can be supplied for locknuts and threaded ends
- Durable and reusable
- Excellent sealing, tight hold and easy assembly

SPECIFICATIONS:

Size Range: ¼" to 3 ¾" diameter bolt or stud Min Height: 3/8" Max Height: 8"
Standard Operating Temperature (°F): Min: -84 Max: +210°



ADVANCE PRODUCTS & SYSTEMS, INC.

P.O. Box 60399 · LAFAYETTE, LA 70596-0399
800-315-6009 · (337) 233-6116 · FAX (337) 232-3860
WEBSITE: WWW.APSONLINE.COM EMAIL: SALES@APSONLINE.COM
ISO-9001 CERTIFIED COMPANY- FM537405