



Call us at 800-315-6009

or

337-233-6116

Email: sales@apsonline.com

Visit: www.apsonline.com

**Please indicate the following when ordering
Casing Spacers, Insulators and End Seals**

*****PROJECT REFERENCE AND LOCATION*****

METAL INSULATORS

- Model number - SI (steel) or SSI (stainless steel)
- Carrier pipe OD, including coating thickness, for concrete or mortar lines: +/- OD tolerance will be needed
- OD of bell or mechanical joint
- Casing ID & OD, casing wall thickness
- Type or size of runner
- Height and width of runner
- Configuration - clear bell, centered, centered and restrained, or non-centered and restrained
- Carrier pipe type and weight per foot



PLASTIC INSULATORS

- Carrier pipe OD including coating thickness
- OD of bell or mechanical joint
- Casing ID & OD
- Casing wall thickness
- Configuration - clear bell, centered, centered and restrained, or non-centered and restrained
- Carrier pipe type and weight per foot



END SEALS

- Model: AC (pull on), AW (wrap around), AZ (zipper), AM (molded), AMCE (cone)
- Carrier pipe OD including coating thickness
- Casing OD
- Configuration - centered or non-centered



Model AC



Model AMCE



Model AW



Model APC Cluster



Model APC Cluster Front View



Model AZ