

Product Summary

Accessories for your chemical pipeline needs.



Flange Isolating Gasket Kits

Full, raised face, or ring joint gaskets; in Buna-N faced phenolic, Durabla, NEMA Grade G-3, G-7, G-10 and G-11 with accompanying isolating double washers of phenolic, Mylar, Nomex, G-10 and one piece bolt sleeves of Minlon. The Trojan and Quad seal G-10 gaskets are also NSF-61 approved. Sizes available from 1/2" to 150" diameter.

Integra II SSA® Gaskets

Dependable gaskets used for both insulating and general sealing purposes in severe service applications. Suitable in all services up to ANSI 2500# and API 15,000# classes. Exclusively designed for hard environmental applications, especially where hydrocarbons are a factor.

Integra II SSAFS® Gaskets

API 6FB approved fire-safe isolation gasket kits that provide exceptionally dependable isolating and sealing capabilities for severe service applications. Featuring a seal that can withstand temperatures up to 1292° F and proprietary coated hardened steel washers. Available in classes up to ANSI 2500# and API 10,000#.

Integra SSAHS® Gaskets

Provides cathodic protection in applications where aggressive chemicals, including hydrogen sulfide and dry & liquid chlorine, are used. Suitable for applications up to and including ANSI 2500# and APS 10,000# classes. Seal temperature range is -350°F to 520°F (-212°C to 271°C) .

Kleerband® Flange Protector

Prevents corrosion from developing between flanges on piping systems and allows for visual inspection of flange cavity. Clear extruded polymer band with air tight D-seal, grease injection fitting and relief vent plug. Kleerband® wraps around the flange and is also available as a stainless steel gasket. All sizes available.

Kleergel®

This high-performance grease executes well at high and low temps (-50 °F to 375 °F). Dielectric and hydrophobic, NSF H-1 certified "food-grade" lubricant. Non-flammable, non-staining, non-toxic, & environmentally safe.

Radolid® Nut & Bolt Protection Caps

Bolt and nut protection caps are used to prevent corrosion on fasteners. Injection molded of low density polyethylene. Available in sizes from 1/4" to 3 3/4" bolt diameter.

Innerlynx® Modular Mechanical Seals

Molded rubber pipe wall penetration seals can be used in treatment plants, valve vaults, tanks and containment dikes. Available in EPDM, nitrile, silicone, and UL three hour fire-rated styles.

Foreman Nite Caps

Cast aluminum temporary pipe plugs, sizes 2" to 48". Prevents unwanted foreign materials, small animals, mud or water from contaminating a pipeline.

UBolt-Cote® and Atlas® Pipe Support Pads

Polyolefin or fusion applied polymer coated UBolts used for corrosion resistance and cathodic protection. Atlas® pipe support pads provide zero water absorption, UV protection and minimal contact between pad and pipe, eliminating crevice corrosion. High temperature HT & XT materials available.

Inspect-a-Lift® Pipe Supports

Prevents crevice corrosion at pipe supports by eliminating standing water. Allows for easy inspection to DOT compliance and no metal to metal contact.

Raq-gard®

Lightweight, injection-molded, glass-filled polymer isolators that eliminate corrosion between pipes and I-beams .

Safety Spray Shields

Safety Spray Shields are designed to prevent injury from a hazardous chemical spray out at flange, valve, expansion joint and fitting connections. Materials range from PTFE, polypropylene, PVC, polyethylene, and stainless steel to cover nearly all applications.

Polyethylene Spacers

Manufactured from injection-molded, high density polyethylene. Used to support and space a section of pipe inside a secondary pipe on dual containment systems. Grooves molded into the inner surface prevent slippage and cold flow. Sizes available from 2" to 12" with a standard runner height of 1".

