







Advance Products & Systems, LLC.
P.O. Box 60399
Lafayette, LA 70596-0399
Phone: 337-233-6116 Fax: 337-232-3860
E-mail: sales@apsonline.com
Website: www.apsonline.com

AWWA C207 Gasket Specification

Please fill out the appropriate sections of the following form in order for APS to manufacture your gasket correctly.

SECTION A Type of Connection			SECTION E Type of Material Needed																														
Note: For raise face flanges please add the raise face thickness to the flange thickness when entering flange thicknesses below Flange #1  Type: Ring Hub Blind Class B D E F Flange I.D. : _____ Flange Thickness : _____ # of Tapped Holes : _____  Valve Connection Valve I.D. : _____ Flange Thickness : _____ # of Tapped Holes : _____			Note: If flanges are not identical, you must specify both flange thicknesses for sleeve to fit properly; <u>Standard Calculations:</u> Sleeve Length Calculations: THK#1 + THK#2 + GASKET THK + 0.0625 = LENGTH Sleeve Length for Tapped Holes: THK#1 + (GASKET THICKNESS) + 0.0625 = LENGTH Flange #2  Type: Ring Hub Blind Class B D E F Flange I.D. : _____ Flange Thickness : _____ # of Tapped Holes : _____  Valve Connection Valve I.D. : _____ Flange Thickness : _____ # of Tapped Holes : _____			Note: Check One Type of Material for Each Item. Gasket: Phenolic Nitrile-Coated Phenolic G-10 Other: _____ Seal: Nitrile Viton PTFE EPDM (Duplex Only) Note: Only G-10 Gasket Material with EPDM or PTFE Seals are NSF61 Approved. Sleeve: G-10 Integral Mylar G-10 Integral Other: _____ Washer: Micarta G-10 Backup Washer: Steel Stainless (304) Stainless (316) Other: _____																											
SECTION D Type of Gasket Needed  <u>Type E</u> Gasket O.D. (O.D. of Flange)  <u>Type F</u> Gasket O.D. (B.C. - B.H. - 1/16")			Quantiy of Seals (per Side): Single Duplex (Two) Quantity of Washers: Single Double																														
SECTION D <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">NOMINAL SIZE:</th> <th colspan="2">PRESSURE CLASS:</th> </tr> </thead> <tbody> <tr> <td>FLANGE O.D.</td> <td>O.D.</td> <td>BOLT SIZE</td> <td>B.S.</td> </tr> <tr> <td>ACTUAL GASKET I.D.</td> <td>I.D.</td> <td>SHOULDER BOLT DIAMETER</td> <td>SHO</td> </tr> <tr> <td>FLANGE I.D.</td> <td>Flg. I.D.</td> <td>RAISED FACE O.D.</td> <td>RFOD</td> </tr> <tr> <td>BOLT CIRCLE DIAMETER</td> <td>B.C.D.</td> <td>CUSTOM SLEEVE LENGTH</td> <td>SLV.</td> </tr> <tr> <td>BOLT HOLE QTY.</td> <td># HOLES</td> <td>SLEEVE LENGTH FOR TAPPED HOLES</td> <td>SLV. TAPPED</td> </tr> <tr> <td>BOLT HOLE SIZE</td> <td>B.H.</td> <td></td> <td></td> </tr> </tbody> </table>			NOMINAL SIZE:		PRESSURE CLASS:		FLANGE O.D.	O.D.	BOLT SIZE	B.S.	ACTUAL GASKET I.D.	I.D.	SHOULDER BOLT DIAMETER	SHO	FLANGE I.D.	Flg. I.D.	RAISED FACE O.D.	RFOD	BOLT CIRCLE DIAMETER	B.C.D.	CUSTOM SLEEVE LENGTH	SLV.	BOLT HOLE QTY.	# HOLES	SLEEVE LENGTH FOR TAPPED HOLES	SLV. TAPPED	BOLT HOLE SIZE	B.H.			Comments: Company Name: _____ Signature: _____ Date: _____		
NOMINAL SIZE:		PRESSURE CLASS:																															
FLANGE O.D.	O.D.	BOLT SIZE	B.S.																														
ACTUAL GASKET I.D.	I.D.	SHOULDER BOLT DIAMETER	SHO																														
FLANGE I.D.	Flg. I.D.	RAISED FACE O.D.	RFOD																														
BOLT CIRCLE DIAMETER	B.C.D.	CUSTOM SLEEVE LENGTH	SLV.																														
BOLT HOLE QTY.	# HOLES	SLEEVE LENGTH FOR TAPPED HOLES	SLV. TAPPED																														
BOLT HOLE SIZE	B.H.																																

Disclaimer: This version may not be the most current revision. Please visit www.apsonline.com to verify that you are utilizing the most current revision.