# **Product Summary**

Accessories for your industrial & mechanical pipeline needs.





# Flange Isolating Gasket Kits

Full, raised face, or RTJ gaskets available in Buna-N faced phenolic, Durabla, NEMA Grade G-3, G-7, G-10 or G-11 from sizes ½" through 144" diameter. Isolating sleeves and washers are available in various materials for kits and include an electroplated steel washer. Also available are duplex four seal G-10 gaskets certified to NSF-61.



#### Innerlynx® Modular Mechanical Seals

Designed to absorb vibrations, shocks, and sound waves, acting as a sound dampener and electrically isolating the carrier pipe from the penetrated structure. Available in EPDM, nitrile, silicone, or UL three hour fire-rated materials and 21 sizes for pipe diameters ranging from 1/2" through 144".



## Kleerband® Flange Protector

Prevents corrosion and foreign material from lodging between the flange faces of piping systems. Clear-extruded polymer band with airtight D-seal allows for visual inspection of flange cavity and includes a grease injection fitting and relief vent plug. Stainless steel flange protectors are also available for extreme temperature applications. Sizes available from 1/2" through 144" diameter.



# Infinity® Wall Sleeves

Lightweight concrete barriers designed for circular penetration through walls, floors, and ceilings. Manufactured of HDPE in sizes 2" through 25", they can withstand 40 psig when combined with Innerlynx® Modular Mechanical Seals.



### **Kleergel®**

This non-flammable, non-staining, and non-toxic synthetic grease maintains good viscosity over wide temperature ranges (-50° F to 375° F), is 100% waterproof, dielectric, and is enhanced with anti-wearing, anti-rusting, and anti-oxidative additives.



#### Gal-Vo-Plast® Wall Sleeves

These wall sleeves provide a better seal than a core drilled hole and feature a proprietary coating system offering superior durability, longer life, and faster availability compared to galvanized wall sleeves. Available in stainless steel, carbon steel, custom lengths and sizes 2" through 120" diameter.



## Radolid® Nut & Bolt Protection Caps

Manufactured of high density UV-resistant polyethylene, these caps are reusable and will keep nuts and bolts corrosion free for years. Available in sizes from 1/4" to 3 3/4" bolt diameter.



## **External Mount Split Wall Sleeves**

Designed for sealing pipe penetrations through walls, floors, and ceilings in atypical scenarios. This wall sleeve is available in Gal-Vo-Plast® steel, stainless steel, or plain steel materials and can be installed after cement has been poured.



## **Casing End Seals**

Full conical end seals available in AC Pull On, AW Wrap-Around, AZ Zipper, AM Molded, AMCE Molded Cone, and APC Cluster, made of 1/8" thick synthetic rubber, accommodates any combination of pipe sizes and secured with stainless steel banding straps with a 100% non-magnetic worm gear screw.



## **UBolt-Cote® and Atlas Pipe Support® Pads**

Polyolefin or fusion applied polymer-coated UBolts used for corrosion resistance and cathodic protection. Atlas Pipe Support® Pads provide zero water absorption, UV protection and minimal contact between pad and pipe, eliminating crevice corrosion. High-temperature HT & XT materials available.